



KOMORI LITHRONE LSX 29-6 (1c+C+DU+5c+C+DU+C)

Reference	22036199
Type	6 colors
Manufacturer	Komori
Model	LITHRONE LSX 29-6 (1c+C+DU+5c+C+DU+C)
Year	2008
Serial Number	135
N.of Impressions	5

[REQUIRE MORE INFO-QUOTATION](#)

[VIEW DETAILS-GALLERY-VIDEO](#)

Accessories

- PDC-SII : Spectral Print Density Control Modello SII
- PQC-S: touch console for ink, axial, circumferential diagonal + all wash-up remote control
- KMS-IV : Komori Management System (Jobs, Report, Maintenance, Errors)
- Komori KHS: de inking and pre inking system
- Feeler foot with ionizing antistatic blower
- Ultrasonic double-sheet control
- Mechanic double sheet control
- Suction belts on table feeder
- Micrometric adjustment of the lateral pull pay by touch panel +/- 3 mm.
- Optical fiber precision photocell system for front and side control + safety photocell for the sheet in advance
- Automatic machine lock through over-register sensor
- Retractable sheet guide selectable by touch panel for sheet cleaning
- Set for Cardboard printing
- Ink ductor temperature control
- Automatic roller wash-up device
- Inks de-clutching device on all the printing units
- Automatic blanket washers
- Automatic impression cylinder wash-up device
- Speed Acceleration: damping roller with accelerated peripheral speed
- FAPC Automatic plate change without folding in side tale and with sequence (does not require the presence of the operator)
- Mechanical compensator for the contact between the rollers
- Skeleton Transfer cylinders with Venturi system
- 3 Ink Oscillating Form Roller Refrigeration complete with ink temperature control
- Remote adjustment of the timing of the pick-up roller

- No. 1 UV interdeck dryer moveable between each unit
- Komorimatic damping
- Technotrans alpha.c ink temp control combined with damping refrigeration + Automix
- No. 3 Tresu L30 Combi double pumps
- Lock/unlock clamps of blanket on the varnishing unit without using tools
- No. 3 UV lamps and IR/Hot Air
- Non-stop on feeder
- AMR (Automatic Make Ready): automatic preset for pressure, size format, autoplate, ink, etc.,
- Weko powder spray device
- IR-Dryer & Hot Air system
- 1° unit=fist printing unit
- 2° unit C= flexo coating unit
- 3° unit DU= UV Dryer unit
- 4°,5°,6°,7°,8 units 5c= no. 5 printing units
- 9° unit C= flexo coating unit TRESU with doctor chamber system
- 10° unit DU= UV Dryer unit
- 11° unit C= flexo coating unit TRESU with doctor chamber system
- Set for printing on plastic and metallic substrates