



## HEIDELBERG XL75-5 LX3 C-Hybrid

<b>Reference</b>	23036341
<b>Type</b>	5 colors
<b>Manufacturer</b>	Heidelberg
<b>Model</b>	XL75-5 LX3 C-Hybrid
<b>Year</b>	2008
<b>Serial Number</b>	LS000022
<b>N.of Impressions</b>	85

[REQUIRE MORE INFO-QUOTATION](#)

[VIEW DETAILS-GALLERY-VIDEO](#)

### Accessories

- Prinect Press Center console touch screen, axial, circumferential and diagonal register remote control, ink ductors rotation control, job memorization
- Prinect Press Center MasterLevel
- Axis Control : spectrophotometric quality control
- Press Center InstantStar
- Press Center Color Assistant
- Prinect Press Center InstantGate
- Pile height sensor
- Pneumatic side register control with integrated auto cleaning and double sheet control with direct system
- Suction belt on feeder
- Double sheet detector - pulling device
- Ultrasonic double-sheet detector
- Antistatic on feeder Advanced
- StaticStar Compact : No. 2 Eltex ion blowers on feeder, antistatic bars on feeder and delivery
- Alcolor damping with Vario system
- Double diameter impression cylinders
- Double diameter transfer cylinder between printing units, with Air Transfer System with possibility to adjust automatically it based on thickness of material to print
- Roller wash-up device controlled by Prinect Press Center
- Blanket and impression cylinders automatic washing devices by Prinect Press Center
- CombiStar CAN beta.c 160 G: Tecnotrans ink temp control combined with damping refrigeration + Alcosmart AZR
- No. 2 x IST/UV interdeck dryers to put in all transfer positions (full flexibility)
- ZDT preparation after unit 1°, 2°, 3°, 4°, 5°
- Coating Star : heat coater system
- Varnishing unit, with cooking register, Tresu chambered doctor blade system, with anilox roller
- Coating pump for dual Hydro and UV circulation system

- UV package coating unit
- Weko AP232 powder spray device
- Delivery with UV package
- DryStar 2000 Combination via CanOpen (5 slide-in dryers) : pos. 1 dryer slide-in unit IR/HA hot air; pos. 2 HA hot air; pos. 3 dryer slide-in unit IR/HA hot air; pos. 4 No. x2 IST UV lamps; pos. 5 KL cold air
- ScrollStar : Atlas Copco compressor
- Technotrans Beta.t
- AirStar : central air box water cooled
- Speed 15.000 c/h
- Preset : automatic size device on feeder & delivery with pressure adjustment by Prinect
- UV basic equipment